

**IN THE CLAIMS:**

Please cancel claim 13 and amend the claims, as follows:

1. (currently amended) A method for simultaneously determining multiple individual chemical concentrations of a liquid kraft liquor stream comprising:
- subjecting at least a segment of the stream to ultraviolet light wherein the light penetrates a short distance into the segment and the effective path length of the light is a function of the refractive index of the segment;
- generating an ultraviolet absorption spectrum from said ultraviolet penetration of the sample over a wavelength from 190 to 300 nm; and
- analyzing the ultraviolet absorption spectrum by a regression method to determine the component concentrations of the liquid stream.
2. (original) A method according to claim 1 wherein the sample is subjected to ultraviolet light by an ATR-UV probe.
3. (original) A method according to claim 1 wherein the sample is subjected to ultraviolet light by an ATR-UV Tunnel flow cell.
4. (original) A method according to claim 1 wherein the regression method is multivariate.
5. (original) A method according to claim 4 wherein the multivariate regression method is the partial least squares method.
6. (original) A method according to claim 1 wherein the regression method is linear.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

7. (original) A method according to claim 1 wherein the stream is a kraft liquor stream.

8. (previously amended) A method according to claim 7 wherein the measured individual chemical concentrations of the kraft liquor are selected from sodium hydroxide, sodium sulfide, and sodium carbonate.

9. (previously amended) A method for simultaneously determining the sodium hydroxide, sodium sulfide, and sodium carbonate concentrations of a kraft liquor stream comprising:

generating an ATR-UV absorbency spectrum of the liquor over a wavelength of 190 to 300 nm;

analyzing the ultraviolet absorption spectrum by a regression method to determine the concentrations of sodium hydroxide, sodium sulfide, and sodium carbonate in the liquor.

10. (previously amended) A method according to claim 9, further comprising controlling operation of a kraft cooking digester recausticizing unit, white liquor oxidization reactor or chemical recovery furnace in response to the determined sodium hydroxide, sodium sulfide, and sodium carbonate concentrations.

11. (currently amended) A system for simultaneously determining multiple individual chemical concentrations of a liquid kraft pulp stream comprising: an ultraviolet spectrophotometer in cooperative relationship with a device capable of providing ultraviolet absorption data between 190 and 300 nm, and a multivariate or linear calibration program for analyzing the ultraviolet absorption data.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

c1  
12. (original) A system according to claim 11 wherein the device is an ATR optical probe.

13. / (cancelled).

14. (original) A system according to claim 11 wherein the device is an ATR tunnel flow cell.

15. (original) A system according to claim 14 wherein the ATR tunnel flow cell is installed in the ultraviolet spectrometer and a kraft liquor stream flows through the ATR tunnel flow cell.

16. (original) A system for determining chemical concentrations of NaOH and Na<sub>2</sub>CO<sub>3</sub> in a kraft liquor stream comprising:

an ultraviolet spectrometer,

c1  
an attenuated total reflectance device capable of providing ultraviolet absorption data between 190 and 300 nm wherein the attenuated total reflectance device transmits the ultraviolet absorption data to the ultraviolet spectrometer by fiber optic cable,

a multivariate or linear calibration program for analyzing the ultraviolet absorption data.

17. (original) A system according to claim 16 wherein the attenuated total reflectance device is an ATR optical probe installed in a kraft liquor stream.

18. (original) A system according to claim 16 wherein the attenuated total reflectance device is an ATR tunnel flow cell installed in the ultraviolet spectrometer and a kraft liquor stream flows through the ATR tunnel flow cell.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com

19. (previously presented) The system according to claim 18, wherein the draft liquor stream is pumped through the ATR tunnel flow cell.

20. (previously presented) The system according to claim 15, wherein the draft liquor stream is pumped through the ATR tunnel flow cell.

C1  
21. (previously presented) The system according to claim 18, further comprising a light source which directs light through the ATR tunnel flow cell to the ultraviolet spectrometer.

22. (previously presented) The system according to claim 15, further comprising a light source which directs light through the ATR tunnel flow cell to the ultraviolet spectrometer.

23. (previously presented) The system according to claim 18, wherein said kraft liquor stream flowing through the ATR tunnel flow cell is not subjected to dilution.

24. (previously presented) The system according to claim 15, wherein said kraft liquor stream flowing through the ATR tunnel flow cell is not subjected to dilution.

FINNEGAN  
HENDERSON  
FARABOW  
GARRETT &  
DUNNER LLP

1300 I Street, NW  
Washington, DC 20005  
202.408.4000  
Fax 202.408.4400  
www.finnegan.com